

Product Description


- **Dimensions** Size plank 914,4 x 152,4 x 5 mm,
- **Packaging** Planks / box = 15 = 2,09 m² (16,43 kg)
Boxes / pallet = 63 = 131,67 m² (1057 kg)
- **Composition**
 1. Top coating, made of polyurethane
 2. Wear layer with printed design film underneath
 3. Solid PVC backing
 4. Unique HIPS (High Impact polystyrene) click frame
 5. Acoustic dampening backing
- **Features** Micro V bevel on 4 sides
- **Click system** Glueless revolutionary mechanical locking system
- **Installation** see box / www.dreamclick.be

Size plank 36" x 6" x 0.20"

Planks / box = 15 = 22,49 sq ft (36.81lb)

Boxes / pallet = 63 = 1,416.87 sq ft (2,354 lb)


Tile and plank construction:



Requirements

Classification Requirements class 23/33/42

Characteristics	Method	Value
Total thickness	EN 428	5,00 mm/.20 inches
Wear layer	EN 429	055 mm/ 22 MIL
Total weight	EN 430	8 kg/m ² (.5lbs/ft ²)
Surface treatment		PUR
Usage classification	EN 685	23 - 33 - 42
Underfloor heating	EN 12524	suitable - max. 27°
Castor chair	EN 425	pass
Fire resistance	EN 13501-1	Bfl-s1
Slip resistance	DIN 51130	R 10
	EN 13983	class DS
Sound reduction	EN ISO 717-2 (□ LW)	8 dB
Light fastness	ISO 105-B02	> 6
Drum noise	EPLF	SL60
Locking strength		500 kg/m
Anti static	EN 1815	yes
Formaldehyde emission	EN 717-1	E1
Chemical resistance	EN 423/ASTM F925	OK / No effect 24 hrs
Residual indentation	EN 433/ASTM F1914	< 0,10 mm / 4%
Coefficient of Friction	ASTM C1028	84 Dry 86 Wet
Ptical Density of Smoke	ASTM E662	435 Flaming 546 Non Flaming
Durometer Hardness	ASTM D2240	97
Radiant Flux	ASTM 648	Class 1
Abrasion resistance	ASTM D3389	.050 mg
Surface Burning characteristics warranty (Res / Com)	ASTM E84	Flame spread 60 Smoke Dev 850 lifetime/ 10 years



Warranty and maintenance

- **Residential warranty:** Lifetime, commercial warranty: 10 years
- **Warranty conditions, care and maintenance:** see www.berryalloc.com

